

CS10 Floor Paint

Date: 14-06-2017

Page: 1

DESCRIPTION

CS10 Floor paint in Grey or Red.

BINDERS

- A.) Long-oil (soya) Alkyd Resin
B.) Thixotropic Long-oil Alkyd Resin

ADDITIVES

Lead-free combined driers, anti-skinning agent, solvent (white spirit)

VOC CONTENT

39.86 By weight.

% SOLIDS BY WEIGHT

60.13

SPECIFIC GRAVITY

1.04 ± 1.0 %

VISCOSITY

4.0 Poise – cone and plate viscometer

FINENESS OF GRIND

8 Hegman

DRYING TIMETouch dry – 2½ – 4 hours
Hard dry – 8 hours – overnight**RECOATABILITY TIME**

Preferably after 24 hours

COVERAGE RATE

Average 10 square meters per Litre

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.