

Safety Data Sheet

IMPACAR RUOTE

Safety Data Sheet dated 27/5/2015, version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: IMPACAR RUOTE

Trade code: 1205

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Paint for metal

Uses advised against:

Not suitable for use in homemaker (DIY) applications.

1.3. Details of the supplier of the safety data sheet

Supplier:

IMPA Spa - Via Crevada 9/E - 31020 SAN PIETRO DI FELETTO (TV) - ITALY

Competent person responsible for the safety data sheet:

msdsref@impa.it

1.4. Emergency telephone number

IMPA Spa - Phone ++39-0438-4548 - Fax ++39-0438-454915 (8.30 - 17.30)


SECTION 2: Hazards identification


2.1. Classification of the substance or mixture


Directive criteria, 67/548/EEC, 1999/45/EC and following amendments thereof:

Properties / Symbols:

Toxic for reproduction category 3

 F Highly flammable

 Xn Harmful

 Xi Irritant

R Phrases:

R11 Highly flammable.


R36/38 Irritating to eyes and skin.


R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.


R63 Possible risk of harm to the unborn child


R67 Vapours may cause drowsiness and dizziness.


EC regulation criteria 1272/2008 (CLP):


 Danger, Flam. Liq. 2, Highly flammable liquid and vapour.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, Repr. 2, Suspected of damaging the unborn child.

 Warning, STOT SE 3, May cause drowsiness or dizziness.

 Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Symbols:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

Safety Data Sheet

IMPACAR RUOTE

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe fume/gas/mist/vapours/spray.

P280 Wear protective gloves/clothing and eye/face protection.

P312 Call a POISON CENTER/ doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special Provisions:

None

Contains:

toluene

ethyl acetate

2.3. Other hazards

No other known hazard

vPvB Substances: None - PBT Substances: None

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>= 15% - < 20% toluene

REACH No.: 01-2119471310-51, Index number: 601-021-00-3, CAS: 108-88-3, EC: 203-625-9

F, Repr. Cat. 3, Xn, Xi; R11-38-48/20-63-65-67

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.7/2 Repr. 2 H361

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.8/3 STOT SE 3 H336

>= 15% - < 20% ethyl acetate

REACH No.: 01-2119475103-46, Index number: 607-022-00-5, CAS: 141-78-6, EC: 205-500-4

F, Xi; R11-36-66-67

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 10% - < 12.5% Aromatic hydrocarbons, C8

REACH No.: 01-2119486136-34, CAS: 90989-38-1, EC: 292-694-9

Xn, Xi; R10-20/21-65-48/20-36/37/38

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.9/2 STOT RE 2 H373

DECLJ*

Safety Data Sheet

IMPACAR RUOTE

>= 7% - < 10% isobutyl acetate

REACH No.: 01-2119488971-22, Index number: 607-026-00-7, CAS: 110-19-0, EC: 203-745-1
F; R11-66

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 5% - < 7% propan-2-ol

REACH No.: 01-2119457558-25, Index number: 603-117-00-0, CAS: 67-63-0, EC: 200-661-7
F,Xi; R11-36-67

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

>= 3% - < 5% n-butyl acetate

REACH No.: 01-2119485493-29, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1
R10-66-67

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 1% - < 3% 2-methylpropan-1-ol

REACH No.: 01-2119484609-23, Index number: 603-108-00-1, CAS: 78-83-1, EC: 201-148-0
Xi; R10-37/38-41-67

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.8/3 STOT SE 3 H336

>= 1% - < 3% Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

REACH No.: 01-2119463258-33, EC: 919-857-5

Xn; R10-65-66-67

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.8/3 STOT SE 3 H336

EUH066

DECLP*

>= 1% - < 3% 2-butoxyethanol

REACH No.: 01-2119475108-36, Index number: 603-014-00-0, CAS: 111-76-2, EC: 203-905-0

Xn,Xi; R20/21/22-36/38

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

*DECLJ: Substance classified accordingly to Note J of the Annex I of directive 67/548/EEC. The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.1% weight/weight of benzene

*DECLP: Substance classified accordingly to Note P of the Annex I of directive 67/548/EEC. The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.1% weight/weight of benzene

Safety Data Sheet

IMPACAR RUOTE

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None known

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO₂, powder extinguisher, foam, water spray.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Do not inhale explosion and/or combustion gases (carbon monoxide, carbon dioxide, oxides of nitrogen).

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Suitable material for collection: inert absorbent material (e.g. sand, vermiculite)

After the product has been recovered, rinse the area and materials involved.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet

IMPACAR RUOTE

Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Electrical equipment must be protected in compliance with appropriate norms.
Do not allow to dry.
Avoid shock and friction.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep the containers tightly closed.
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
See chapter 10.5
Instructions as regards storage premises:
Keep container tightly closed in a cool, well-ventilated place, away from heat.

7.3. Specific end use(s)

See chapter 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

toluene - CAS: 108-88-3

WEL -- Country: UNITED KINGDOM - LTE: 191 mg/m³, 50 ppm - STE: 384 mg/m³, 100 ppm

EU - LTE(8h): 192 mg/m³, 50 ppm - STE: 384 mg/m³, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH, 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

ethyl acetate - CAS: 141-78-6

ACGIH, 400 ppm - Notes: URT and eye irr

WEL -- Country: UNITED KINGDOM - LTE: 730 mg/m³, 200 ppm - STE: 1460 mg/m³, 400 ppm

Aromatic hydrocarbons, C8 - CAS: 90989-38-1

ACGIH - LTE: 434 mg/m³, 100 ppm - STE: 651 mg/m³, 150 ppm

isobutyl acetate - CAS: 110-19-0

ACGIH, 150 ppm - Notes: Eye and URT irr

WEL -- Country: UNITED KINGDOM - LTE: 724 mg/m³, 150 ppm - STE: 903 mg/m³, 187 ppm

propan-2-ol - CAS: 67-63-0

ACGIH, 200 ppm, 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair

WEL -- Country: UNITED KINGDOM - LTE: 999 mg/m³, 400 ppm - STE: 1250 mg/m³, 500 ppm

n-butyl acetate - CAS: 123-86-4

ACGIH, 150 ppm, 200 ppm - Notes: Eye and URT irr

WEL -- Country: UNITED KINGDOM - LTE: 724 mg/m³, 150 ppm - STE: 966 mg/m³, 200 ppm

2-methylpropan-1-ol - CAS: 78-83-1

ACGIH, 50 ppm - Notes: Skin and eye irr

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

ACGIH - LTE: 1200 mg/m³, 197 ppm

2-butoxyethanol - CAS: 111-76-2

WEL -- Country: UNITED KINGDOM - LTE: 123 mg/m³, 25 ppm - STE: 246 mg/m³, 50 ppm

EU - LTE(8h): 98 mg/m³, 20 ppm - STE: 246 mg/m³, 50 ppm - Notes: Bold-type:

Safety Data Sheet

IMPACAR RUOTE

Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH, 20 ppm - Notes: A3, BEI - Eye and URT irr

DNEL Exposure Limit Values

Aromatic hydrocarbons, C8 - CAS: 90989-38-1

Worker Professional: 0.077 mg/l - Consumer: 0.0148 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

Aromatic hydrocarbons, C8 - CAS: 90989-38-1

Target: Marine water - Value: 0.327 mg/l

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Fresh Water - Value: 12.46 mg/kg

Target: Soil (agricultural) - Value: 2.31 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Skin protection:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Hands protection:

Use protective gloves that provides comprehensive protection, e.g. NBR (nitrile rubber), FKM (fluoro rubber).

The selection of suitable gloves does not only depend on the material, but also on other quality characteristics and varies from manufacturer to another one, and on the manner and times of use of the mixture.

Respiratory protection:

Combination filtering device (DIN EN 141).

Environmental exposure controls:

See chapter 6.2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour: thick liquid

Odour: of solvent

Odour threshold: nd

pH: nd

Melting point / freezing point: nd

Initial boiling point and boiling range: nd

Solid/gas flammability: na

Upper/lower flammability or explosive limits: nd

Vapour density: nd

Flash point: < 23 °C

Evaporation rate: nd

Vapour pressure: nd

Relative density: 0.98 ± 0.02

Solubility in water: not soluble

Solubility in oil: nd

Partition coefficient (n-octanol/water): nd

Auto-ignition temperature: nd

Decomposition temperature: nd

Viscosity: 110 ÷ 180 sec. ISO-DIN cup 6 mm (20°C)

Explosive properties: none

Oxidizing properties: none

Safety Data Sheet

IMPACAR RUOTE

9.2. Other information

Miscibility: nd
Conductivity: nd

Legend:

na = not applicable - nd = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

It may generate dangerous reactions (See subsections below)

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and nitrides.

Because of heat or fire the preparation can release carbon oxides and vapours which may be harmful to health.

Aluminium, copper or brass, acids or acidic resins, amines/aminoalcohols or amino-resins, oxidizing agents may cause exothermic reaction (generating heat and fumes) and/or self-ignition by catalytic decomposition with cellulose nitrate.

10.4. Conditions to avoid

Avoid to keep near heat sources.

10.5. Incompatible materials

Avoid contact with oxidizing materials or powerful oxidising agents. The product could catch fire.

10.6. Hazardous decomposition products

No hazardous decomposition products when stored and handled correctly.

See chapter 5.2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Possible risk of harm to the unborn child

Toxic for reproduction category 3

Toxicological information of the main substances found in the mixture:

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5542 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 14000 mg/kg

ethyl acetate - CAS: 141-78-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rabbit 5620 mg/kg

Aromatic hydrocarbons, C8 - CAS: 90989-38-1

a) acute toxicity:

Test: LC50 - Route: Inhalation Vapour - Species: Rat 27124 mg/m³ - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat 3223 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 12126 mg/kg

propan-2-ol - CAS: 67-63-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5050 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 12800 mg/kg

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 10000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat 21.1 mg/l - Duration: 4h

2-methylpropan-1-ol - CAS: 78-83-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 2460 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 2460 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat 19.2 mg/l - Duration: 4h

Safety Data Sheet

IMPACAR RUOTE

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 4951 mg/m³

2-butoxyethanol - CAS: 111-76-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 470 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 220 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat 2.17 mg/l - Duration: 4h

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

Adopt sound working practices, so that the product is not released into the environment.

12.1. Toxicity

Ecotoxicological studies of the product are not available.

Aromatic hydrocarbons, C8 - CAS: 90989-38-1

a) Aquatic acute toxicity:

Endpoint: IC50 - Species: Algae 2.2 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia 1.0 mg/l - Duration h: 24

Endpoint: LC50 - Species: Fish 2.6 mg/l - Duration h: 96

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



Safety Data Sheet

IMPACAR RUOTE

- 14.1. UN number
 ADR-UN Number: 1263
 IATA-UN Number: 1263
 IMDG-UN Number: 1263
- 14.2. UN proper shipping name
 ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
 IATA-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
 IMDG-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
- 14.3. Transport hazard class(es)
 ADR-Class: 3
 ADR - Hazard identification number: 33
 IATA-Class: 3
 IATA-Label: 3
 IMDG-Class: 3
- 14.4. Packing group
 ADR-Packing Group: II
 IATA-Packing group: II
 IMDG-Packing group: II
- 14.5. Environmental hazards
 ADR-Environmental Pollutant: No
 IMDG-Marine pollutant: No
- 14.6. Special precautions for user
 ADR-Subsidiary risks: -
 ADR-S.P.: 163 640C 650
 ADR-Tunnel Restriction Code: (D/E)
 IATA-Passenger Aircraft: 353
 IATA-Subsidiary risks: -
 IATA-Cargo Aircraft: 364
 IATA-S.P.: A3 A72
 IATA-ERG: 3L
 IMDG-EmS: F-E , S-E
 IMDG-Subsidiary risks: -
 IMDG-Storage category: Category B
 IMDG-Storage notes: -
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
 N.A.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
 Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)
 Dir. 1999/45/EC (Classification, packaging and labelling of dangerous preparations)
 Dir. 98/24/EC (Risks related to chemical agents at work)
 Dir. 2000/39/EC (Occupational exposure limit values)
 Dir. 2006/8/EC
 Regulation (EC) n. 1907/2006 (REACH)
 Regulation (EC) n. 1272/2008 (CLP)
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 Regulation (EU) n. 453/2010 (Annex I)
 Regulation (EU) n. 286/2011 (ATP 2 CLP)
 Regulation (EU) n. 618/2012 (ATP 3 CLP)
 Regulation (EU) n. 487/2013 (ATP 4 CLP)

Safety Data Sheet

IMPACAR RUOTE

Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)

Volatile Organic compounds - VOCs = 69.55 %

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Where applicable, refer to the following Italian regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

R10 Flammable.

R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

R37/38 Irritating to respiratory system and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H361 Suspected of damaging fertility or the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H319 Causes serious eye irritation.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H318 Causes serious eye damage.

H302 Harmful if swallowed.

EUH066 Repeated exposure may cause skin dryness or cracking.

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 11: Toxicological information

SECTION 15: Regulatory information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

Safety Data Sheet

IMPACAR RUOTE

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold
CCNL - Appendix 1 "TLV for 1989-90"

Safety data sheets of raw materials suppliers.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.	Not Applicable / Not Available