

TECHNICAL DATA SHEET

CS10 Anti-Silicone Additive

Date: 21-06-2017 Page: 1

What causes "FISH EYES"

- 1. Oil, wax, grease or silicone contamination.
- 2. Contaminated air lines.
- 3. Polishes, aerosol spray that contain silicone (some interior cleaners).
- 4. Contamination by overspray of an incompatible paint system.

Health and Safety Statement

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist FOR PROFESSIONAL USE ONLY. Read full instructions before use.

Prevention

Thoroughly degrease surface with good quality wax/grease remover FL2023. Add Final Systems Anti-Silicone additive to top coat. Regular maintenance of air supply/equipment.

Directions

Anti-Silicone additive is for use in automotive and industrial urethanes to improve levelling and eliminate fisheyes and crater formation. For best results, mix 1 reservoir per quart (litre) of clear or topcoat, add hardener and reducer where required, mix thoroughly and leave to condition for 10 minutes.

Limitations

Do not exceed recommended levels of addition.

Do not use in primer systems.

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application.

Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.