

## Safety Data Sheet

### ACCORD

Safety Data Sheet dated 4/2/2015, version 1

---

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ACCORD

Trade code: 3087

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Recommended use:

Polyester putty for body shop

1.3. Details of the supplier of the safety data sheet

Supplier:

IMPA Spa - Via Crevada 9/E - 31020 SAN PIETRO DI FELETTO (TV) - ITALY

Competent person responsible for the safety data sheet:

msdsref@impa.it

1.4. Emergency telephone number

IMPA Spa - Phone ++39-0438-4548 - Fax ++39-0438-454915 ( 8.30 - 17.30 )


---

#### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Directive criteria, 67/548/EEC, 1999/45/EC and following amendments thereof:

Properties / Symbols:

 Xn Harmful

 Xi Irritant

R Phrases:


R10 Flammable.


R20 Harmful by inhalation.


R36/37/38 Irritating to eyes, respiratory system and skin.

R48 Danger of serious damage to health by prolonged exposure.


EC regulation criteria 1272/2008 (CLP):

 Warning, Flam. Liq. 3, Flammable liquid and vapour.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, Repr. 2, Suspected of damaging the unborn child.

 Danger, STOT RE 1, Causes damage to organs through prolonged or repeated exposure (hearing organs).

2.2. Label elements

Symbols:



Danger

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure (hearing organs).

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

## Safety Data Sheet

### ACCORD

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P314 Get medical advice/attention if you feel unwell.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P405 Store locked up.

#### Special Provisions:

PACK1 The packing must be featured by a safety lock for children.  
PACK2 The packing must have tactile indications of danger for blind people.

#### Contains:

styrene

#### 2.3. Other hazards

No other known hazard

vPvB Substances: None - PBT Substances: None

---

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>= 12.5% - < 15% styrene

REACH No.: 01-2119457861-32, Index number: 601-026-00-0, CAS: 100-42-5, EC: 202-851-5

Repr. Cat. 3,Xn,Xi; R10-20-36/38-48/20-63

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.7/2 Repr. 2 H361d

⚠ 3.9/1 STOT RE 1 H372

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 0.5% - < 1% toluene

REACH No.: 01-2119471310-51, Index number: 601-021-00-3, CAS: 108-88-3, EC: 203-625-9

F,Repr. Cat. 3,Xn,Xi; R11-38-48/20-63-65-67

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.7/2 Repr. 2 H361

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.8/3 STOT SE 3 H336

< 0.1% (2-methoxymethylethoxy)propanol

REACH No.: 01-2119450011-60, CAS: 34590-94-8, EC: 252-104-2

substance with a Community workplace exposure limit

---

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

## Safety Data Sheet

### ACCORD

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed  
None known

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

#### SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO<sub>2</sub>, powder extinguisher, foam, water spray.

Extinguishing media which must not be used for safety reasons:

Water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Do not inhale explosion and/or combustion gases (carbon monoxide, carbon dioxide, oxides of nitrogen).

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Suitable material for collection: inert absorbent material (e.g. sand, vermiculite)

After the product has been recovered, rinse the area and materials involved.

6.4. Reference to other sections

See also section 8 and 13

---

#### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

## Safety Data Sheet

### ACCORD

Keep away from food, drink and feed.

See chapter 10.5

Instructions as regards storage premises:

Keep container tightly closed in a cool, well-ventilated place, away from heat.

7.3. Specific end use(s)

See chapter 1.2

---

## SECTION 8: Exposure controls/personal protection

8.1. Control parameters

styrene - CAS: 100-42-5

ACGIH, 20 ppm, 40 ppm - Notes: A4, BEI - CNS impair, URT irr, peripheral neuropathy

WEL -- Country: UNITED KINGDOM - LTE: 430 mg/m<sup>3</sup>, 100 ppm - STE: 1080 mg/m<sup>3</sup>, 250 ppm

toluene - CAS: 108-88-3

WEL -- Country: UNITED KINGDOM - LTE: 191 mg/m<sup>3</sup>, 50 ppm - STE: 384 mg/m<sup>3</sup>, 100 ppm

EU - LTE(8h): 192 mg/m<sup>3</sup>, 50 ppm - STE: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH, 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

(2-methoxymethylethoxy)propanol

- CAS: 34590-94-8

EU - LTE(8h): 308 mg/m<sup>3</sup>, 50 ppm - Notes: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH, 100 ppm, 150 ppm - Notes: Skin - Eye and URT irr, CNS impair

DNEL Exposure Limit Values

styrene - CAS: 100-42-5

Worker Professional: 0.289 mg/l - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 0.085 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 0.306 mg/l - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Professional: 406 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

styrene - CAS: 100-42-5

Target: Fresh Water - Value: 0.028 mg/l

Target: Marine water - Value: 0.0028 mg/l

Target: Freshwater sediments - Value: 0.614 mg/kg

Target: Marine water sediments - Value: 0.0614 mg/kg

Target: Soil (agricultural) - Value: 0.2 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Skin protection:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Hands protection:

Use protective gloves that provides comprehensive protection, e.g. NBR (nitrile rubber), FKM (fluoro rubber).

The selection of suitable gloves does not only depend on the material, but also on other quality characteristics and varies from manufacturer to another one, and on the manner and times of use of the mixture.

Respiratory protection:

Combination filtering device (DIN EN 141).

## Safety Data Sheet

### ACCORD

Environmental exposure controls:  
See chapter 6.2

---

#### SECTION 9: Physical and chemical properties

##### 9.1. Information on basic physical and chemical properties

Appearance and colour:	thick paste
Odour:	of styrene
Odour threshold:	nd
pH:	nd
Melting point / freezing point:	nd
Initial boiling point and boiling range:	nd
Solid/gas flammability:	na
Upper/lower flammability or explosive limits:	nd
Vapour density:	nd
Flash point:	> 23 °C
Evaporation rate:	nd
Vapour pressure:	nd
Relative density:	1.84 ± 0.02
Solubility in water:	not soluble
Solubility in oil:	nd
Partition coefficient (n-octanol/water):	nd
Auto-ignition temperature:	nd
Decomposition temperature:	nd
Viscosity:	nd
Explosive properties:	none
Oxidizing properties:	none

##### 9.2. Other information

Miscibility:	nd
Conductivity:	nd

Legend:

na = not applicable - nd = not available

---

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

Stable under normal conditions

##### 10.2. Chemical stability

Stable under normal conditions

##### 10.3. Possibility of hazardous reactions

Contact with Organic Peroxides cause a fast mass thickening with considerable development of heat.

Because of heat or fire the preparation can release carbon oxides and vapours which may be harmful to health.

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

##### 10.4. Conditions to avoid

Avoid to keep near heat sources.

High temperature reduces product shelf-life causing spontaneous thickening.

##### 10.5. Incompatible materials

Avoid contact with oxidizing materials or powerful oxidising agents. The product could catch fire.

See chapter 10.3

##### 10.6. Hazardous decomposition products

No hazardous decomposition products when stored and handled correctly.

See chapter 5.2

---

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

## Safety Data Sheet

### ACCORD

Toxicological information of the main substances found in the mixture:

styrene - CAS: 100-42-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat 11.8 mg/l - Duration: 4h

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5542 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 14000 mg/kg

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

#### SECTION 12: Ecological information

Adopt sound working practices, so that the product is not released into the environment.

12.1. Toxicity

Ecotoxicological studies of the product are not available.

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

---

#### SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

#### SECTION 14: Transport information



14.1. UN number

ADR-UN Number: 3269

IATA-UN Number: 3269

IMDG-UN Number: 3269

14.2. UN proper shipping name

ADR-Shipping Name: POLYESTER RESIN KIT

## Safety Data Sheet

### ACCORD

IATA-Shipping Name:	POLYESTER RESIN KIT
IMDG-Shipping Name:	POLYESTER RESIN KIT
14.3. Transport hazard class(es)	
ADR-Class:	3
ADR - Hazard identification number:	-
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
14.4. Packing group	
ADR-Packing Group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
14.5. Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
14.6. Special precautions for user	
ADR-Subsidiary risks:	-
ADR-S.P.:	236 340
ADR-Tunnel Restriction Code:	(E)
IATA-Passenger Aircraft:	370
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	370
IATA-S.P.:	A66 A163
IATA-ERG:	3L
IMDG-EmS:	F-E , S-D
IMDG-Subsidiary risks:	-
IMDG-Storage category:	Category A
IMDG-Storage notes:	-
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
N.A.	

---

### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)
  - Dir. 1999/45/EC (Classification, packaging and labelling of dangerous preparations)
  - Dir. 98/24/EC (Risks related to chemical agents at work)
  - Dir. 2000/39/EC (Occupational exposure limit values)
  - Dir. 2006/8/EC
  - Regulation (EC) n. 1907/2006 (REACH)
  - Regulation (EC) n. 1272/2008 (CLP)
  - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
  - Regulation (EU) n. 453/2010 (Annex I)
  - Regulation (EU) n. 286/2011 (ATP 2 CLP)
  - Regulation (EU) n. 618/2012 (ATP 3 CLP)

Volatile Organic compounds - VOCs = 1.19 %

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Where applicable, refer to the following Italian regulatory provisions :

- Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.
- 1999/13/EC (VOC directive)

- 15.2. Chemical safety assessment  
No

## Safety Data Sheet

### ACCORD

---

#### SECTION 16: Other information

Text of phrases referred to under heading 3:

R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R36/38 Irritating to eyes and skin.  
R38 Irritating to skin.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R63 Possible risk of harm to the unborn child  
R65 Harmful: may cause lung damage if swallowed.  
R67 Vapours may cause drowsiness and dizziness.

H226 Flammable liquid and vapour.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure (hearing organs).  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H225 Highly flammable liquid and vapour.  
H361 Suspected of damaging fertility or the unborn child.  
H304 May be fatal if swallowed and enters airways.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H336 May cause drowsiness or dizziness.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU. This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold  
CCNL - Appendix 1 "TLV for 1989-90"

Safety data sheets of raw materials suppliers.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
CAS: Chemical Abstracts Service (division of the American Chemical Society).  
CLP: Classification, Labeling, Packaging.  
DNEL: Derived No Effect Level.  
EINECS: European Inventory of Existing Commercial Chemical Substances.  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
IATA: International Air Transport Association.  
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
ICAO: International Civil Aviation Organization.  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
IMDG: International Maritime Code for Dangerous Goods.



## Safety Data Sheet

### ACCORD

INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.	Not Applicable / Not Available