

CS10 Plastic Primer

Date: 29-10-2019

Page: 1

DESCRIPTION

CS10 Plastic Primer is a specially formulated adhesion promoter to help promote the adhesion between the plastic substrate and the topcoat. CS10 can be applied on many plastic substrates including the following plastics AAS, PC/PET, PETP, PP-E, PP+E/P, PP/EPDM, TSOP. Ensure surface is correctly prepared with a p240 -p320 and thoroughly degrease. Contact FLP Group for any queries regarding this product.

MIXING RATIO

Ready for use – Shake well before using

FLUID SETUP

1.0-1.2mm

Pressure: 2.0 bar (30 psi inlet)

Refer to manufacturer's recommendation

APPLICATION

1-2 light coats

FLASH OFF TIME

5 minutes between coats

RECOATING

Recoat after 15min @ 20°C. Don't leave for more than 1hour before over coating or plastic primer will need scotching.

HEALTH AND SAFETY

Please refer to Material Safety Data Sheet.

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application.

Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.