

TECHNICAL DATA SHEET

ULTIMATE High Adhesion Promoter

Date: 06-Jun-2023

DESCRIPTION

ULTIMATE High Adhesion Promoter is an single component primer based on special olefin resins.

Composition:	Special Olefin Resins
Colour:	Clear
Shelf life:	12 months in unopened container
Pack size:	1 Litre
Pre-treatment:	FL8015 ULTIMATE HIGH ADHESION PROMOTER should be applied under primer. Fast-drying primer/bonding agent that enables painting of various substrates with 2K products and UV-curing paints. Example materials include plastics (ABS, PP, PET, PA, urea, Bakelite), Glass and Metals (chrome, nickel, tinplate, zamak, aluminium and alloys in general also by PVD-SPUTTERING technique).

	Health and safety “For professional use only” Important: When using any new product, consult the “Health and Safety” data sheet. Always read the risks and precautions stated on the product label.
This is a ready for use product	
	Spraying Viscosity 13” – 15” ASTM 4 at 20°C
	HVLP spray gun fluid tip 1.1 – 1.3 2 Bar Pressure
	Number of coats 2 First coat: light coat 3 minute flash off Second coat: full coat
	Flash off 5-10 minutes

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.