



KAPCI
COATINGS

For professional use only

Issue: March 2015

Kapci 400 NC Putty

Product description

Kapci 400 is an extra rapid 1K putty based on a nitrocellulose resins blend. It is used for fine and smooth leveling of minor irregularities, scratches, and pores.

Substrates

Kapci 400 NC putty should be applied in thin layers over 2K PE putties, primers/fillers, glass fiber reinforced plastic (GRP), and old paints previously sanded properly.

Application



Application:

Apply by knife. Apply in 1-2 thin coats.

When necessary repeat the operation more times. Allow drying for 5-10 minutes between coats.



Drying time at 20°C:

Dry to sand: approximately 20 min



Machine or manual dry sanding:

The following grades of sanding papers are recommended:
P400 or P500



Manual wet sanding:

The following grades of sanding papers are recommended:
P800 or P1000

These products are for the professional painting of automotive vehicles only after reference to the manufacturer's Material Safety Data Sheets (MSDS).



KAPCI
COATINGS

For professional use only

Issue: March 2015

General notes

Recoatable

Kapci 400 is recoatable after sanding.

Other tips

1. After applying Kapci 400 NC putty clean used tools with NC thinner.

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and suitable protective equipment must be worn while using these products.
4. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: These products are for professional use only. The information in this Technical Data Sheet is based on our best knowledge and given for information purposes only without any obligation as we do not have control over the quality and conditions of the surface, or over many factors affecting the use and application of the product. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available.