Printing date 29.03.2015

Revision: 29.03.2015

	ation of the substance/mixture and of the company/undertaking
Product id	entifier
	ne: <u>Kapci 611.</u>
	lentified uses of the substance or mixture and uses advised against relevant information available.
	n of the substance / the mixture 1263
	the supplier of the safety data sheet
	irer/Supplier:
Kapci Coa	
Industrial . Port Said	Zone El - Raswa
EGYPT	
mohamed.	rashad@kapci.com
	formation obtainable from: Product safety department
Emergenc	<i>x telephone number:</i> During normal opening times: +20 66 3770000
Hazanda	identification
	v v
	ion of the substance or mixture ion according to Regulation (EC) No 1272/2008
	GHS02 flame
Flam. Liq.	2 H225 Highly flammable liquid and vapour.
	GHS07
Acute Tox.	4 H332 Harmful if inhaled.
Skin Irrit. 2	2 H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H335 May cause respiratory irritation.
Classificat	ion according to Directive 67/548/EEC or Directive 1999/45/EC
Xn; I	Iarmful
R20/21:	Harmful by inhalation and in contact with skin.
Xi; Iı	ritant
R36/37/38	Irritating to eyes, respiratory system and skin.
<i>F; H</i>	ghly flammable
R11:	Highly flammable.
Informatio	n concerning particular hazards for human and environment:
	ct has to be labelled due to the calculation procedure of the "General Classification guideline j
preparatio Classificat	ns of the EU" in the latest valid version. ion system:
	ication is according to the latest editions of the EU-lists, and extended by company and literati
data.	- · · · · ·
Label elen	
Labelling	according to Regulation (EC) No 1272/2008 ct is classified and labelled according to the CLP regulation.

Printing date 29.03.2015

Revision: 29.03.2015

Trade	name:	Kapci	<i>611</i> .
-------	-------	-------	--------------

II	(Contd. of page 1)
Hazard picto	ograms
\wedge	\wedge
< M> <	
	•
GHS02 C	GHS07
011502	511507
Signal word	Danger
	rmining components of labelling:
xylene	
4-methylpen	
Hazard state	
	v flammable liquid and vapour.
	ful if inhaled.
	s skin irritation.
H319 Cause	s serious eye irritation.
	ause respiratory irritation.
Precautiona	ry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361	+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
	with water/shower.
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, a
	present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/internationa
	regulations.
Other hazar	
Results of P.	BT and vPvB assessment

• *PBT:* Not applicable. • *vPvB:* Not applicable.

3 Composition/information on ingredients

• (Chemical	charact	erisation	: Mixtures
-----	----------	---------	-----------	------------

• Description: Mixture of substances listed below with nonhazardous additions.

CAS: 1330-20-7	xylene	20-35%
EINECS: 215-535-7	Xn R20/21; Xi R38 R10	
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 108-10-1	4-methylpentan-2-one	20-35%
EINECS: 203-550-1	Xn R20; Xi R36/37; 🔥 F R11 R66	
	Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 84540-57-8	methoxypropyl acetate	10-25%
EINECS: 283-152-2	R10	
· Additional informat	ion: For the wording of the listed risk phrases refer to section 16.	1

(Contd. on page 3)

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 611.

(Contd. of page 2)

4 First aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*

(Contd. on page 4)

ЗB

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 611.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients	with limit	values that	require	monitoring	at the	workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

108-10-1 4-methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one

· Additional information: The lists valid during the making were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

GB

(Contd. of page 3)

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 611.

(Contd. of page 4) Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

• Information on basic physical and ch • General Information	emical properties
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	114 °C
· Flash point:	14 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	333 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	9.0 Vol %
· Vapour pressure at 20 °C:	8 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
• Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water)	: Not determined.
· Viscosity:	
Dynamic:	Not determined.

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 611.

		(Contd. of page 5)
Kinematic:	Not determined.	
· Solvent content: Organic solvents: VOC (EC)	54.0 % 54.00 %	
Solids content: • Other information	21.0 % No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/L	· LD/LC50 values relevant for classification:				
1330-	1330-20-7 xylene				
Oral	LD5	50	4300 mg/kg (rat)		
Derm	al LD5	50	2000 mg/kg (rabbit)		
108-1	108-10-1 4-methylpentan-2-one				
Oral	LD5	50	2080 mg/kg (rat)		
Derm	al LD5	50	16000 mg/kg (rab)		
Inhald	ative LC5	50/4 h	8.3-16.6 mg/l (rat)		

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

⁻ GB

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 611.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number · ADR, IMDG, IATA	UN1263
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
Transport hazard class(es)	
· ADR, IMDG, IATA	
- Class - Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	11
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ)	1L
	(Contd. on page

(Contd. of page 6)

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 611.

	(Contd. of page 7)
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN1263, PAINT, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R36/37 Irritating to eyes and respiratory system.
- R38 Irritating to skin.
- *R66 Repeated exposure may cause skin dryness or cracking.*
- · Department issuing MSDS: Product safety department
- · Contact: Mr. Rashad
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- STOT SE 3: Specific target organ toxicity Single exposure, Hazard Category 3