Printing date 29.03.2015

Revision: 29.03.2015

1 Identification of the substance/mixture and of the company/undertaking
· Product identifier
 Trade name: <u>Kapci 625</u> Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the mixture 123456
 Details of the supplier of the safety data sheet Manufacturer/Supplier: Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.rashad@kapci.com
• Further information obtainable from: Product safety department • Emergency telephone number: During normal opening times: +20 66 3770000
2 Hazards identification
• Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008
GHS02 flame
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Repr. 2 H361d Suspected of damaging the unborn child.
GHS07
Skin Irrit. 2 H315 Causes skin irritation.
Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xn; Harmful
R63: Possible risk of harm to the unborn child.
<i>F; Highly flammable</i>
R11: Highly flammable. • Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. • Classification system:
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
(Contd. on page 2

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 625

· Hazard pict	(Contd. of page 1)
	GHS07 GHS08
· Signal word	Danger
	ermining components of labelling:
toluene	
Hazard stat	
	lly flammable liquid and vapour.
	ses skin irritation.
	ected of damaging the unborn child.
P101	ury statements If medical advice is needed, have product container or label at hand.
P102	<i>Keep out of reach of children.</i>
P102	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
	+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
D221	with water/shower.
P321	Specific treatment (see on this label).
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazar	

• Other hazards

· **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 1330-20-7	xylene	2-12%
EINECS: 215-535-7	Xn R20/21; Xi R38 R10	
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 108-88-3	toluene	2-12%
EINECS: 203-625-9	🗙 Xn R48/20-63-65; 🗙 Xi R38; 🐞 F R11 R67	
	Repr. Cat. 3	
	 Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336 	
· Additional informat	ion. For the wording of the listed risk phrases refer to section 16	

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)

[·] Results of PBT and vPvB assessment

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 625

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

(Contd. of page 2)

GB

Printing date 29.03.2015

Revision: 29.03.2015

(Contd. of page 3)

Trade name: Kapci 625

· Ingre	edients with limit values that require monitoring at the workplace:	
1330	-20-7 xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
108-8	88-3 toluene	
WEL	Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk	
· Ingre	edients with biological limit values:	
1330	-20-7 xylene	
BMG	 W 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid 	

• Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 5)

GB

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 625

(Contd. of page 4)

Physical and chemical proper	rties
· Information on basic physical and	chemical properties
· General Information	enemieu propernes
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	110 °C
· Flash point:	4 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	500 °C
• Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	14.0 %
VOC (EC)	14.00 %
Solids content:	86.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 29.03.2015

Revision: 29.03.2015

(Contd. of page 5)

Trade name: Kapci 625

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50	· LD/LC50 values relevant for classification:		
1330-20-7	xylene		
Oral	LD50	4300 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
108-88-3 t	108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5320 mg/l (mouse)	

· Primary irritant effect:

• on the skin: No irritant effect.

 \cdot on the eye: No irritating effect.

 \cdot Sensitisation: No sensitising effects known.

 $\cdot \textit{Additional toxicological information:}$

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

 \cdot CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Repr. 2

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

• Persistence and degradability No further relevant information available.

· Behaviour in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)

GB

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 625

(Contd. of page 6)

-	UN1263 1263 PAINT PAINT
ADR IMDG, IATA Transport hazard class(es)	
IMDG, IATA Transport hazard class(es)	
Transport hazard class(es) ADR, IMDG, IATA	PAINI
-	
ADR, IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler): EMS Number:	33 F-E,S-E
Transport in bulk according to Annex II (MARPOL73/78 and the IBC Code	of Not applicable.
	Noi applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2
Excepted quantities (EQ)	<i>Maximum net quantity per inner packaging: 30 ml</i>
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml Maximum net quantity per outer packaging: 500 ml

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

GB

Printing date 29.03.2015

Revision: 29.03.2015

Trade name: Kapci 625

	(Contd. of page
Releva	nt phrases
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
	May be fatal if swallowed and enters airways.
	Harmful in contact with skin.
	Causes skin irritation.
	Harmful if inhaled.
	May cause drowsiness or dizziness.
	Suspected of damaging the unborn child.
	May cause damage to organs through prolonged or repeated exposure.
	Flammable.
	Highly flammable.
	Harmful by inhalation and in contact with skin.
	Irritating to skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.
Depart	ment issuing MSDS: Product safety department
Contac	t: Mr. Rashad
Abbrev	iations and acronyms:
	cord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internation
	e of Dangerous Goods by Road)
	nternational Maritime Code for Dangerous Goods
	ternational Air Transport Association obally Harmonised System of Classification and Labelling of Chemicals
	European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances
CAS: Ch	emical Abstracts Service (division of the American Chemical Society)
	vlatile Organic Compounds (USA, EU)
	ethal concentration, 50 percent
	ethal dose, 50 percent q. 2: Flammable liquids, Hazard Category 2
	q. 2: Flammable liquids, Hazard Category 2 q. 3: Flammable liquids, Hazard Category 3
	x. 4: Acute toxicity, Hazard Category 4
	t. 2: Skin corrosion/irritation, Hazard Category 2
Repr. 2: 1	Reproductive toxicity, Hazard Category 2
	3: Specific target organ toxicity - Single exposure, Hazard Category 3
	2 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox.	. 1: Aspiration hazard, Hazard Category 1