Printing date 12.07.2010

Revision: 12.07.2010

**1** Identification of the substance/preparation and of the company/undertaking

- · Product details
- · Trade name: Kapci 651
- $\cdot$  Application of the substance / the preparation 1

• Manufacturer/Supplier: Kapci Coatings Industrial Zone El - Raswa Port Said EGYPT mohamed.rashad@kapci.com

· Further information obtainable from: Product safety department

• Information in case of emergency: During normal opening times: +20 66 3770000

## **2** Hazards identification

- · Hazard description: Not applicable.
- · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 67 Vapours may cause drowsiness and dizziness.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· GHS label elements



H226 - Flammable liquid and vapour.

Warning

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

- · Prevention:
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- · Response:
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

*P321* • *Storage:* 

P405 Store locked up.

· Disposal:

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

#### · Chemical characterization

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
	n-butyl acetate		20-35%	
EINECS: 204-658-1		Warning: 🚸 2.6/3; <b>()</b> 3.8/3		
CAS: 1330-20-7	xylene	🗙 Xn, 🗙 Xi; R 10-20/21-38	2.5-10%	
EINECS: 215-535-7		Warning: 🚸 2.6/3; 🚸 3.1.D/4, 3.1.I/4, 3.2/2		
·		(Cont	d. on page 2)	

- GB

Printing date 12.07.2010

Revision: 12.07.2010

Trade name: Kapci 651

(Contd. of page 1)

· Additional information: For the wording of the listed risk phrases refer to section 16.

## 4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

## **5** Fire-fighting measures

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

## 6 Accidental release measures

· Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

- *Measures for environmental protection:* Do not allow to enter sewers/ surface or ground water. • *Measures for cleaning/collecting:*
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents

## 7 Handling and storage

#### · Handling:

- Information for safe handling: 1
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

## 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV

• Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.

(Contd. on page 3)

<sup>-</sup> GB

Printing date 12.07.2010

Revision: 12.07.2010

#### Trade name: Kapci 651

· Protection of hands:

(Contd. of page 2)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

· General Information			
Form:	Fluid		
Colour:	According to product specification Characteristic		
Odour:			
· Change in condition			
Melting point/Melting range:	: Undetermined.		
Boiling point/Boiling range:	124°C		
· Flash point:	27°C		
· Ignition temperature:	370°C		
· Self-igniting:	Product is not selfigniting.		
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
· Explosion limits:			
Lower:	1.1 Vol %		
Upper:	7.5 Vol %		
· Vapour pressure at 20°C:	10.7 hPa		
· Density: 0	0.98-1.00 g/cm <sup>3</sup> .		
· Solubility in / Miscibility with			
water:	Not miscible or difficult to mix.		
· Solvent content:			
Organic solvents:	37.0 %		
Solids content:	63.0 %		

## **10 Stability and reactivity**

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. (Contd. on page 4)

Printing date 12.07.2010

Revision: 12.07.2010

(Contd. of page 3)

Trade name: Kapci 651

• Materials to be avoided:

· Dangerous reactions No dangerous reactions known.

· Dangerous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

· Acute toxicity:

· LD/LC50 values relevant for classification:

#### 1330-20-7 xylene

*Oral LD50 4300 mg/kg (rat)* 

Dermal LD50 2000 mg/kg (rabbit)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

#### **12** Ecological information

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

# **13 Disposal considerations**

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

#### **14 Transport information**

· Land transport ADR/RID (cross-border)



• ADR/RID class: 3 Flammable liquids.

- Danger code (Kemler): 30
- · UN-Number:
- · Packaging group:
- · Hazard label:
- Description of goods: 1263 PAINT RELATED MATERIAL

1263

Ш

3

• Tunnel restriction code D/E

(Contd. on page 5)

GR

Printing date 12.07.2010

Revision: 12.07.2010

Trade name: Kapci 651

		(Contd. of page
· Maritime transport IN	MDG:	
3		
· IMDG Class:	3	
· UN Number:	1263	
· Label	3	
· Packaging group:	III	
· EMS Number:	F-E,S-E	
• Marine pollutant:	No	
· Proper shipping nam	e: PAINT RELATED MATERIAL	
· Air transport ICAO-T	I and IATA-DGR.	
111 transport 10/10-1		
3		
ICAO/IATA Class	3	
· ICAO/IATA Class: · UN/ID Number:	5 1263	
· UN/ID Number: · Label	3	
	5 III	
Dashaging groups	111	
· Packaging group:	e: PAINT RELATED MATERIAL	

## **15 Regulatory information**

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

#### · Risk phrases:

10 Flammable.

67 Vapours may cause drowsiness and dizziness.

#### · Safety phrases:

2 Keep out of the reach of children.

25 Avoid contact with eyes.

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant R-phrases

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

- 38 Irritating to skin.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Product safety department
- · Contact: Mr. Rashad

(Contd. on page 6)

GB

Printing date 12.07.2010

Revision: 12.07.2010

#### Trade name: Kapci 651

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. of page 5)