

TECHNICAL DATA SHEET

ULTI-MATT 2K Matting Agent

Date: 01-Jul-2024

DESCRIPTION

ULTI-MATT is a matting agent which is added into 2K paint products or 2K clearcoats to provide a matt, satin or semi-gloss finish.

Add **ULTI-MATT** to **ULTIMATE 2K HS Clearcoat**, **ULTIMATE 2K HS DTM Clearcoat** or **ULTIMATE 2K HS DTM Colour** to create your own gloss level.

APPLICATION





The recommendations below are for guidance only:

	Mixing ratio, % by volume		
	Matt	Satin	Semi-gloss
2K Paint Product	50	60	70
ULTI-MATT	50	40	30

FL2055 **ULTI-MATT 2K Matting Agent** can be applied over solvent and waterborne basecoats when mixed with **ULTIMATE 2K HS Clearcoat**, **ULTIMATE 2K HS DTM Clearcoat** or **ULTIMATE 2K HS DTM Colour**.

We do not recommend topcoats to be polished after application with ULTI-MATT as the polishing process will gloss the top coat.

Composition: Acrylic Resins
Shelf life: 36 months in unopened container
Pack size: 500ml

	Health and safety "For professional use only" Important: When using any new product, consult the "Health and Safety" data sheet. Always read the risks and precautions stated on the product label.
	Shake ULTI-MATT matting agent well before use.
	Mixing Ratio Put into 2K clearcoat or 2K paint product then mix hardener and thinner as per product. Reduce or don't add thinner when ratio of matting agent is high (to prevent poor coverage).
	HTE/RP spray gun fluid tip 1.2 – 1.3 HVLP gravity feed fluid tip 1.2 – 1.5 Recommended Spray Pressure 2 – 2.5 bar
	Number of coats: As per clearcoat or 2K paint product being applied.



For drying times refer to original product ULTI-MATT 2K Matting Agent is be mixed with.
Please note that when using this matting agent it will extend your products drying time.

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.