

## Technical Data Sheet

Date: 29-October-2025  
Product Code: FL2056/1

### ULTI-GRIP Alloy Wheel Promoter 1L

Final Systems ULTI-GRIP Alloy Wheel Promoter is a fast drying, 1K etch primer/bonding agent that enables the ULTIMATE 2K HS Clearcoat to adhere to aluminium substrates including alloy wheels.





For use on materials including Metals (chrome, nickel, tinplate, zamak, aluminium and alloys).


RFU = Ready for Use

#### Preparation

Surfaces must be clean, dry and free from dust, grease, oil or millscale etc. Carry out test spray before application.

#### Application

	<p>Health and safety "For professional use only"</p> <p>Important: When using any new product, consult the "Health and Safety" data sheet. Always read the risks and precautions stated on the product label.</p>	
	<p>Ready for Use</p> <p>Mix well and filter before use</p>	
	<p>Spray Viscosity</p> <p>1" – 15" ASTM 4 at 20°C</p>	
	<p>Spray Pressure</p> <p>14.5/21.75 PSI (1-1.5 bar)</p>	<p>Spray Gun Fluid Tip</p> <p>HVLP 1.1 – 1.3mm</p>

	No. of Coats: 1	Full coat
	Drying Times	Allow to air dry for 2-5 minutes depending on ambient temperature.  Ensure you apply your ULTIMATE 2K HS Clearcoat within 20 minutes.

### Technical Information

12 month shelf life when correctly stored in closed original container. Always replace and firmly close lid immediately after use.

Size	1L
Colour	Colourless
Composition	Special Olefin Resins
VOC Content	732g/l

### Health & Safety

Refer to relevant Health & Safety or Material Safety Data Sheets.

The technical data contained herein is based on our present knowledge and experience. We cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of the product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.



Scan for the latest  
ULTI-GRIP Alloy Wheel Promoter  
product information

