

Safety Data Sheet

SPRUZZO

Safety Data Sheet dated 15/9/2014, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: SPRUZZO

Trade code: 3300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Spray polyester filler for Body Shop

Uses advised against:

Not suitable for use in homemaker (DIY) applications.

1.3. Details of the supplier of the safety data sheet

Supplier:

IMPA Spa - Via Crevada 9/E - 31020 SAN PIETRO DI FELETTO (TV) - ITALY

Competent person responsible for the safety data sheet:

msdsref@impa.it

1.4. Emergency telephone number


IMPA Spa - Phone ++39-0438-4548 - Fax ++39-0438-454915 (8.30 - 17.30)


SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Directive criteria, 67/548/EEC, 1999/45/EC and following amendments thereof:

Properties / Symbols:

 F Highly flammable

 Xn Harmful

 Xi Irritant

R Phrases:

R11 Highly flammable.


R20 Harmful by inhalation.


R36/37/38 Irritating to eyes, respiratory system and skin.


R48 Danger of serious damage to health by prolonged exposure.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.


EC regulation criteria 1272/2008 (CLP):

 Danger, Flam. Liq. 2, Highly flammable liquid and vapour.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, Repr. 2, Suspected of damaging the unborn child.

 Danger, STOT RE 1, Causes damage to organs through prolonged or repeated exposure (hearing organs)

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Symbols:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

Safety Data Sheet

SPRUZZO

H372 Causes damage to organs through prolonged or repeated exposure (hearing organs)
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P314 Get medical advice/attention if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains:

styrene
cobalt bis(2-ethylhexanoate): May produce an allergic reaction.

2.3. Other hazards

No other known hazard
vPvB Substances: None - PBT Substances: None

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

>= 20% - < 25% styrene

REACH No.: 01-2119457861-32, Index number: 601-026-00-0, CAS: 100-42-5, EC: 202-851-5
Repr. Cat. 3,Xn,Xi; R63-20-48/20-10-36/38

- ⚠ 2.6/3 Flam. Liq. 3 H226
- ⚠ 3.7/2 Repr. 2 H361d
- ⚠ 3.9/1 STOT RE 1 H372
- ⚠ 3.3/2 Eye Irrit. 2 H319
- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 1% - < 3% ethyl acetate

REACH No.: 01-2119475103-46, Index number: 607-022-00-5, CAS: 141-78-6, EC: 205-500-4
F,Xi; R11-36-66-67

- ⚠ 2.6/2 Flam. Liq. 2 H225
 - ⚠ 3.3/2 Eye Irrit. 2 H319
 - ⚠ 3.8/3 STOT SE 3 H336
- EUH066

>= 1% - < 3% toluene

REACH No.: 01-2119471310-51, Index number: 601-021-00-3, CAS: 108-88-3, EC: 203-625-9
F,Repr. Cat. 3,Xn,Xi; R11-38-48/20-63-65-67

- ⚠ 2.6/2 Flam. Liq. 2 H225
- ⚠ 3.7/2 Repr. 2 H361
- ⚠ 3.10/1 Asp. Tox. 1 H304
- ⚠ 3.9/2 STOT RE 2 H373
- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.8/3 STOT SE 3 H336

>= 1% - < 3% Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

REACH No.: 01-2119486291-36, EC: 926-605-8
F,Xn,N; R11-65-66-67-51/53

- ⚠ 2.6/2 Flam. Liq. 2 H225

Safety Data Sheet

SPRUZZO

- ◆ 3.10/1 Asp. Tox. 1 H304
 - ◆ 3.8/3 STOT SE 3 H336
 - ◆ 4.1/C2 Aquatic Chronic 2 H411
- EUH066
DECLP*

>= 0.1% - < 0.5% cobalt bis(2-ethylhexanoate)

- CAS: 136-52-7, EC: 205-250-6
Repr. Cat. 3,Xn,Xi,N; R62-22-50/53-43-38
- ◆ 3.1/4/Oral Acute Tox. 4 H302
 - ◆ 3.7/2 Repr. 2 H361f
 - ◆ 4.1/A1 Aquatic Acute 1 H400
 - ◆ 4.1/C1 Aquatic Chronic 1 H410
 - ◆ 3.2/2 Skin Irrit. 2 H315
 - ◆ 3.4.2/1-1A-1B Skin Sens. 1, 1A, 1B H317

>= 0.1% - < 0.5% Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

- REACH No.: 01-2119458049-33, EC: 919-446-0
Xn,N; R10-66-67-65-51/53
- ◆ 2.6/3 Flam. Liq. 3 H226
 - ◆ 3.10/1 Asp. Tox. 1 H304
 - ◆ 3.8/3 STOT SE 3 H336
 - ◆ 4.1/C2 Aquatic Chronic 2 H411
- EUH066
DECLP*

*DECLP: Substance classified accordingly to Note P of the Annex I of directive 67/548/EEC. The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.1% weight/weight of benzene

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediately and dispose off safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

None known

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:
CO₂, powder extinguisher, foam, water spray.

Safety Data Sheet

SPRUZZO

Extinguishing media which must not be used for safety reasons:

Water jet.

- 5.2. Special hazards arising from the substance or mixture
Burning produces heavy smoke.
Do not inhale explosion and/or combustion gases (carbon monoxide, carbon dioxide, oxides of nitrogen).
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Remove all sources of ignition.
Wear personal protection equipment.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- 6.3. Methods and material for containment and cleaning up
Suitable material for collection: inert absorbent material (e.g. sand, vermiculite)
After the product has been recovered, rinse the area and materials involved.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
See chapter 10.5
Instructions as regards storage premises:
Keep container tightly closed in a cool, well-ventilated place, away from heat.
- 7.3. Specific end use(s)
See chapter 1.2

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
styrene - CAS: 100-42-5
ACGIH - LTE: 85 mg/m³, 20 ppm - STE: 170 mg/m³, 40 ppm
WEL -- Country: UNITED KINGDOM - LTE: 430 mg/m³, 100 ppm - STE: 1080 mg/m³, 250 ppm
ethyl acetate - CAS: 141-78-6
ACGIH - LTE: 1441 mg/m³, 400 ppm

Safety Data Sheet

SPRUZZO

WEL -- Country: UNITED KINGDOM - LTE: 730 mg/m³, 200 ppm - STE: 1460 mg/m³, 400 ppm
toluene - CAS: 108-88-3
EU - LTE: 192 mg/m³, 50 ppm - STE: 384 mg/m³, 100 ppm
WEL -- Country: UNITED KINGDOM - LTE: 191 mg/m³, 50 ppm - STE: 384 mg/m³, 100 ppm
ACGIH - LTE: 75.4 mg/m³, 20 ppm
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
ACGIH - LTE: 300 mg/m³, 52 ppm

DNEL Exposure Limit Values
N.A.

PNEC Exposure Limit Values
N.A.

8.2. Exposure controls

Eye protection:
Use close fitting safety goggles, don't use eye lens.

Skin protection:
Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Hands protection:
Use protective gloves that provides comprehensive protection, e.g. NBR (nitrile rubber), FKM (fluoro rubber).
The selection of suitable gloves does not only depend on the material, but also on other quality characteristics and varies from manufacturer to another one, and on the manner and times of use of the mixture.

Respiratory protection:
Combination filtering device (DIN EN 141).

Environmental exposure controls:
See chapter 6.2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance and colour:	thick liquid
Odour:	of styrene
Odour threshold:	nd
pH:	nd
Melting point / freezing point:	nd
Initial boiling point and boiling range:	nd
Solid/gas flammability:	na
Upper/lower flammability or explosive limits:	nd
Vapour density:	nd
Flash point:	< 23 °C
Evaporation rate:	nd
Vapour pressure:	nd
Relative density:	1.54 ± 0.02
Solubility in water:	not soluble
Solubility in oil:	nd
Partition coefficient (n-octanol/water):	nd
Auto-ignition temperature:	nd
Decomposition temperature:	nd
Viscosity:	33 ÷ 40 sec. ISO-DIN cup 8 mm (20°C)
Explosive properties:	none
Oxidizing properties:	none

9.2. Other information

Miscibility:	nd
Conductivity:	nd

Legend:

Safety Data Sheet

SPRUZZO

na = not applicable - nd = not available

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
Contact with Organic Peroxides cause a fast mass thickening with considerable development of heat.
Because of heat or fire the preparation can release carbon oxides and vapours which may be harmful to health.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- 10.4. Conditions to avoid
Avoid to keep near heat sources.
High temperature reduces product shelf-life causing spontaneous thickening.
- 10.5. Incompatible materials
Avoid contact with oxidizing materials or powerful oxidising agents. The product could catch fire.
See chapter 10.3
- 10.6. Hazardous decomposition products
No hazardous decomposition products when stored and handled correctly.
See chapter 5.2

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects
Toxicological information of the mixture:
N.A.
Toxicological information of the main substances found in the mixture:
styrene - CAS: 100-42-5
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat 2650 mg/kg
Test: LC50 - Route: Inhalation Vapour - Species: Rat 11.8 mg/l - Duration: 4h
ethyl acetate - CAS: 141-78-6
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rabbit 5620 mg/kg
toluene - CAS: 108-88-3
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat 5542 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit 14000 mg/kg
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
a) acute toxicity:
Test: LC50 - Route: Inhalation Vapour - Species: Rat > 20 mg/l - Duration: 4h
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 4 ml/kg
Test: LC50 - Route: Inhalation Vapour - Species: Rat > 13.1 mg/l - Duration: 4h

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;

Safety Data Sheet

SPRUZZO

- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

Adopt sound working practices, so that the product is not released into the environment.

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

a) Aquatic acute toxicity:

- Endpoint: LC50 - Species: Fish 50 mg/l - Duration h: 96
- Endpoint: IC50 - Species: Algae 4.6 mg/l - Duration h: 72
- Endpoint: EC50 - Species: Daphnia 10 mg/l - Duration h: 48

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



14.1. UN number

- ADR-UN Number: 3269
- IATA-UN Number: 3269
- IMDG-UN Number: 3269

14.2. UN proper shipping name

- ADR-Shipping Name: POLYESTER RESIN KIT
- IATA-Shipping Name: POLYESTER RESIN KIT
- IMDG-Shipping Name: POLYESTER RESIN KIT

14.3. Transport hazard class(es)

- ADR-Class: 3
- ADR - Hazard identification number: -
- IATA-Class: 3
- IATA-Label: 3
- IMDG-Class: 3

14.4. Packing group

- ADR-Packing Group: II
- IATA-Packing group: II
- IMDG-Packing group: II

14.5. Environmental hazards

Safety Data Sheet

SPRUZZO

ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
14.6. Special precautions for user	
ADR-Subsidiary risks:	-
ADR-S.P.:	236 340
ADR-Tunnel Restriction Code:	(E)
IATA-Passenger Aircraft:	370
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	370
IATA-S.P.:	A66 A163
IATA-ERG:	3L
IMDG-EmS:	F-E , S-D
IMDG-Subsidiary risks:	-
IMDG-Storage category:	Category B
IMDG-Storage notes:	-
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
N.A.	

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)
 - Dir. 1999/45/EC (Classification, packaging and labelling of dangerous preparations)
 - Dir. 98/24/EC (Risks related to chemical agents at work)
 - Dir. 2000/39/EC (Occupational exposure limit values)
 - Dir. 2006/8/EC
 - Regulation (EC) n. 1907/2006 (REACH)
 - Regulation (EC) n. 1272/2008 (CLP)
 - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 - Regulation (EU) n. 453/2010 (Annex I)
 - Regulation (EU) n. 286/2011 (ATP 2 CLP)
 - Regulation (EU) n. 618/2012 (ATP 3 CLP)

Volatile Organic compounds - VOCs = 5.42 %

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Where applicable, refer to the following Italian regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

15.2. Chemical safety assessment

No

SECTION 16: Other information

Text of phrases referred to under heading 3:

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R22 Harmful if swallowed.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitization by skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety Data Sheet

SPRUZZO

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R63 Possible risk of harm to the unborn child

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

H226 Flammable liquid and vapour.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure (hearing organs)

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.

H361f Suspected of damaging the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

EUH066 Repeated exposure may cause skin dryness or cracking.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

CCNL - Appendix 1 "TLV for 1989-90"

Safety data sheets of raw materials suppliers.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of
Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of
Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport
Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

Safety Data Sheet

SPRUZZO

	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.	Not Applicable / Not Available