

TECHNICAL DATA SHEET

ULTIMATE Super High Build Primer Aerosol







Date: 18-Jan-2024

DESCRIPTION

ULTIMATE Super High Build Primer aerosol is a fast drying super high build primer/filler with excellent finish and sandability. Perfect for smart and spot repairs.

FL6010 **ULTIMATE Super High Build Primer** can be applied under solvent and waterborne basecoats. Etch and plastic primer must be used where applicable.

- Colour:** Black, White or Grey
Shelf life: Correctly stored material, in a cool dry place will have a shelf of 12 months.
Pack size: 400ml Aerosol Can

| | |
|---|--|
|  | <p>Health and safety “For professional use only” Important: When using any new product, consult the “Health and Safety” data sheet. Always read the risks and precautions stated on the product label.</p> |
|  | <p>Clean the surface thoroughly using slow or fast degreaser. Surface must be clean, dry and dust free.</p> |
|  | <p>Shake can well before use 2-3 minutes.</p> |
|  | <p>Apply product spraying 20-25cm away from the surface. DO NOT overload product onto the panel.</p> |
|  | <p>Apply 2 or 3 coats with 2 minutes flash-off in-between coats. Dust free dry in 5 minutes.</p> |
|  | <p>Through cured 10 minutes at 20 °C. Fully dried in 24 hours. Low heat may be used. This primer is infrared compatible.</p> |

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.