

TECHNICAL DATA SHEET







ULTIMATE High Adhesion Promoter - Aerosol

Date: 29-Nov-2023

DESCRIPTION

ULTIMATE High Adhesion Promoter Aerosol is a ready to single component primer based special olefin resins..

Composition:	Special Olefin Resins
Colour:	Clear
Shelf life:	Correctly stored material, in a cool dry place will have a shelf life of 12 months
Pack size:	400ml Aerosol
Pre-treatment:	FL8015 ULTIMATE HIGH ADHESION PROMOTER should be applied under primer. Fast-drying primer/bonding agent that enables painting of various substrates with 2K products and UV-curing paints. Example materials include plastics (ABS, PP, PET, PA, urea, Bakelite), Glass and Metals (chrome, nickel, tinplate, zamak, aluminium and alloys in general also by PVD-SPUTTERING technique).

	Health and safety “For professional use only” Important: When using any new product, consult the “Health and Safety” data sheet. Always read the risks and precautions stated on the product label.
	Surface must be clean, dry and dust free.
	Shake can well before use.
	Apply product spraying 15-20cm away from the panel being sprayed. DO NOT overload product onto the panel.
	Spray 2 coats: Apply 1 light coat followed by 3 minutes flash off, then apply 1 full coat followed by 5-10 minutes. DO NOT apply more than the recommended number of coats. This will cause the products not to fully dry.
	Flash off 5-10 minutes

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.